



CCTV DATA SHEET

SECURITY KIT

8 Channel All in One 1080N DVR + 4 TVI Bullet
IMPX 720P Cameras

MODEL: L-DX841M-ND



1/4 CMOS



WEATHERPROOF



DAY AND NIGHT



MOTION
DETECTION



NOTIFICATION
ALARM



NO MONTHLY
FEES



LOGAN TECHNOLOGY INC.

Address: 8338 NW 66th St, Miami, FL 33166 United States.

Phone: +1800-6409048 / sales@logan-cam.com



Logan Technology
www.logan-cam.com

Video Security System

MODEL: L-DX841M-ND



High-resolution analog HD systems have evolved into different variants, incompatible with each other, such as HD-TVI, AHD and HD-CVI. This has caused that the diverse technologies devices can not compatible. That is why LOGAN offers a new series of All-In-One cameras that allow you to operate in each and every HD protocol variants. Therefore, in the same camera we can select HD-TVI, AHD, HD-CVI and even analog output PAL / NTSC and this can be done without having to enter the on-screen menu. It is only necessary to hold down the joystick button on the cable for 5 seconds for the desired technology: TVI (right), CVI (bottom), AHD (left), composite video (up). By default all-in-one cameras come in AHD.

This reports great benefits when installing larger CCTV systems from various protocols, besides the comfort that supposes for the technicians to carry spare cameras without worries about the type of technology that appears in the installation.

ALL IN ONE SERIES

MODEL: L-DX841M-ND



CCTV Data Sheet

TECHNICAL SPECIFICATIONS FOR DVR	
VIDEO	
Video Input	DVR: 8CH 1080N Hybrid: 4CH 1080N + 4CHIP 960P NVR: 16CHIP 1080P / 9CHIP 1080P / 16CHIP 960P / 4CHIP 5Mpx
Video Output	VGA, HDMI
Display Resolution	Up to 1080P (1920 x 1080)
Display Split	DVR: 1/4/9 Screen Hybrid: 1/4/9 Screen NVR: 1/4/9/16 Screen
AUDIO	
Audio Input	4 Channel RCA
Audio Output	1 Channel RCA
RECORDING	
Record Quality	Up to 1080N DVR mode, up to 1080P NVR mode
Video Compression	H.264 (High Profile)
Record Mode	Manual / Schedule / Motion / Alarms
PLAYBACK	
Simultaneously Playback	1/2/4 Channels
Backup Mode	USB Device, Web Browser, Mobile App
Playback Quality	Up to 1080P (1920 x 1080)
EXTERNAL PORTS	
USB Port	2 Ports, USB 2.0
RS485	1 Port for PTZ Control
Ethernet	1 RJ-45 Port (10/100Mbps)
STORAGE	
HDD Port	2 SATA Port
HDD Capacity	Up to 8TB
GENERAL	
Power Supply	DC 12V/3A
Video System	NTSC/PAL Switch Selectable
Remote Access	Cloud System For Remote Access, NO Port Mapping
Compatibility For	iOS, Android

CAMERA	
Image Sensor	1/4" OV9732 CMOS/720P
Camera Resolution	1 Megapixel
Effective Pixels	1280(H) x 720(V)
Infrared LED	36 pcs
Lens Mount	3,6mm
Format	TVI
Field of View	60° Degrees
Video Output	1CH BNC
Minimum Illumination	0 LUX (IR on)
IR Cut Filter	Yes
Night Vision Distance	66~82ft / 20~25m
Shutter Speed	1/60s~1/67,500s
Operative Temperature	-4° ~ +131°F / -20° ~ +55° C
Ingress Protection	IP66
Video System	NTSC
Power Supply	DC 12V/320mA (IR on)
WHAT'S IN THE BOX	
1 DVR of 8 Channels 4 TVI Bullet Cameras of 1Mpx 720P 4 BNC Cables of 60ft / 18,3m 1 Splitter with 9 ways 1 Mouse 1 AC 100/240V Power Adapter 1 Ethernet Cable 1 Quick Guide 2 Caution Sticker + 1 Installation CD 1 Remote control	



LOGAN HD
FREE APP
 Remote View



Address: 8338 NW 66th St, Miami, FL 33166 United States.
 Phone: +1800-6409048 / sales@logan-cam.com

