

CCTV DATA SHEET

VOLTAGE REGULATOR

2000VA UPS

MODEL: L-PW2000-PLUS



ENERGY SAVING



INTERACTIVE
LINE TECHNOLOGY



COLD START



SMART BATTERY
MANAGEMENT



X8 PLUG



USB PORT

LOGAN TECHNOLOGY INC.

Address: 8338 NW 66th St, Miami, FL 33166 United States.

Phone: +1800-6409048 / sales@logan-cam.com



Logan Technology
www.logan-cam.com

CCTV Data Sheet

TECHNICAL SPECIFICATIONS FOR THE UPS	
GENERAL	
Model	L-PW2000-PLUS
Capacity	2000VA
INPUT	
Voltage	100/240V AC
Voltage Range	89-145V AC
Frequency Range	60 o 50 Hz (auto recognition)
OUTPUT	
AC Voltage Regulation (Battery Mode)	±10%
Frequency Range (Battery Mode)	60 o 50 Hz ±1Hz
Transfer time	Typical 2-6 ms
Waves (Battery Mode)	Simulated Sine Wave
BATTERY	
Voltage	12V DC
Dimensions D x W x H (mm)	380x158x198
ENVIRONMENTAL SPECIFICATIONS	
Humidity	0-90% (unfused)
Temperature	0-40°C
Noise level	Less than 40dB