

## Fingerprint Access Control Terminal Kit

TECHNICAL SPECIFICATIONS	
Operation system	Linux
Storage	Up to 3000 Valid Cards Up to 100,000 Event Records Up to 150,000 Attendance Records
Fingerprint capacity	Up to 3000 Valid Fingerprints, Up to 10 Fingerprints for Each Person
Fingerprint Comparing Mode	1:1 and 1:N, N=3000
Card Reading Response Duration	< 1 s
Fingerprint Authentication Duration	< 1 s
FAR (False Accept)	≤ 0.001 %
FRR (False Rejection Rate)	≤ 0.01 %
Fingerprint Recognizer	Optical Fingerprint Recognizer Module
External Card Reader	Standard Wiegand26/34
Keyboard	Keyboard (Back Light)
Reset Key	x 1
Communication Interface	TCP/IP, RS-485 (For Secure Door Control Unit), Wiegand Output (W26/W34) and Input (Wiegand26/34)
Wi-Fi	Support
Wiegand Interface	Output: Wiegand 26/34; Input: Wiegand 26/34
Transmission Rate	TCP/IP: 10/100Mbps, Self-adaptive; RS485: 19200 bps-N-8-1
Input Interface	Exit Button x 1, Door Sensor x 1 and Alarm input x 1
Output Interface	Relay (Lock Output) x 1, and Alarm Output x 1
USB	USB 2.0 ; Type A
LCD Screen	2.4-inch (320 x 240 LCD-TFT Display Screen)
Audio	1 Buzzer and 1 Loudspeaker
LED Indicator	Power/Status (Red/Green)
Power Supply	12 VDC / 2 A
Working Temperature	-10 °C to 55 °C (14 ° F to 131° F)
Working Humidity	10% to 90% (No Condensing)
Water-Proof	IP42
Temper-Proof	Support
Dimension (L x W x H)	205 mm x 76.5 mm x 37 mm (8.07" x 1.46")
Installation	Surface Mounting, Metal Door Mounting, Installation with Gang Box



**MODEL: LACK261-LBP**

## APPEARANCE

